

Cold Transfer-Sheet-fed Offset-Metallic-CF6.2S

UV overprintable metallized Cold Transfer Product for Sheet-fed Offset Printing



Characteristic

- UV overprintable cold transfer product for use on sheet-fed offset presses in conjunction with oxidative drying and UV-curing adhesives
- Good edge definition with optimized release behavior
- Suitable for surfaces to fine fonts and lines
- Very good overprintability with conventional / oxidative drying and UV-curing inks
- Very good adhesion to oxidative / conventional drying glues and numerous UV-curing inks
- High production speeds of over 10,000 gph are possible

Areas of application

- Applicable on sheetfed offset presses with cold transfer module
- Suitable for a wide variety of coated image printing as well as for coated folding boxboards

Processing parameters

- Optimized application quantity: 1.5 - 3.0 g/m² depending on the absorbency of the substrate
- Carefully test the suitable adhesive for your specific print product. Adapt the adhesive application to the properties of the substrate. It is recommended to overcoat the cold transfer application accordingly to achieve sufficient abrasion and rub resistance.

Available colors



● S-01



● G-220

● Standard product. Mostly on stock.

○ These products are available on order. Small quantities may be available. A minimum order quantity applies.

The colors shown here are for reference only, are technically generated and not binding. Please ask for one of our original color guides for this product. Other colors and gloss levels are available on request.

Formats

Core size

Available on 3 inch and 6 inch cardboard core.

Product width

Various roll sizes available - please inquire!

Running meters per roll

Various roll sizes available - please inquire!

Certificates

**REACH
SVHC**



sqts⁺

**FDA
APPROVED**



94/62/EC



Under optimum transfer conditions, all our products have a high to very high gloss (except satin and matt products) and high abrasion and rub resistance. However, as these values depend on many production parameters and not least on the substrate and printing process used, we cannot give any measured values here.

All United Transfer products have been developed for their respective specific applications. However, experience shows that substrates, printing machines and operating conditions can vary. Therefore, users of our products are urged to verify that the selected product types are suitable for their specific applications by making test prints under production conditions. For this purpose, samples are available from us upon request. If you need assistance, we will be happy to provide advice and support.

For safe storage we recommend to leave the product in its original packaging, store in a cool, dry place without direct sunlight. The product should be processed within one year from the indicated production date.

All information and recommendations are given by us in good faith on the basis of our practical experience - but without guarantee. We refer to our general terms and conditions of sale and terms of delivery.

For further information, please visit: www.unitedtransfer.com